

Startex™



LONDON WHITE



WHITE



BISQUE



CREAM



CLOUD

Hightex™



COFFEE CREAM



WHITE RICE



BEACH



STONE

Sandtex™



OYSTER



GREIGE



SAGE BRUSH



EARLY SKY

Ropetex®



SNOWDRIFT



FROSTY



FRENCH BEIGE



PUMICE

FabRICTEX®



DOVER



PEARL



SAND



GREY FLANNEL

Meritex™



CREAM OF WHEAT



SANDSTONE



ALMOND



INDIGO

Woodtex®



WHEATWOOD™



HONEYWOOD™

Woodtex® PREMIUM



SORRELWOOD™

Lustertex™



BRUSHED ALUMINUM



CANYONWOOD™



SABLEWOOD™



EBONY ASH



RAVENWOOD™



SILKWOOD™



BRUSHED PEWTER

PLEASE NOTE: Customers should always obtain the actual color selections card or samples before specifying as computer monitors and color printers vary in their ability to display color.

SCOPE

Panelfold’s **Vinyltex™** vinyl color selections are an attractive, durable and economical design solution available on Panelfold product models as indicated below:

	Scale®	Sonicwal®	Fabricwal®	Moduflex®	PrimeSpacer®
Startex FILM TYPE I TYPE II	●	●			
				●	●
			N/A	▲	▲
Sandtex TYPE I TYPE II	▲	▲		●	●
			●	▲	▲
Fabrictex TYPE I TYPE II	▲	▲		●	●
			●	▲	▲
Hightex TYPE I TYPE II	▲	▲		●	●
			●	▲	▲
Ropetex TYPE I TYPE II	▲	▲		●	●
			●	▲	▲
Meritex TYPE I TYPE II	▲	▲		●	●
			●	▲	▲
Woodtex FILM	▲	▲	N/A	Series 400/600 Only ▲	▲
Lustertex FILM	▲	▲	N/A	Series 400/600 Only ▲	▲

● Standard ▲ Upgrade

FIRE RESISTANCE

All Panelfold vinyl surfaces have been tested for Class A fire hazard classification in accordance with ASTM E-84 Tunnel Test Method (Surface Burning Characteristics of Building Materials).

	FILM	TYPE I	TYPE II
Flame Spread	10	10	5 or 10
Smoke Density	0 or 15	25	5

NOTE: The numerical flame spread rating and other test results referenced herein are not intended to reflect hazards presented by this or any other materials under actual fire conditions.

PERFORMANCE

Panelfold vinyls have low static properties, are non-allergenic, and will not mildew, rot or support the growth of bacteria.

MAINTENANCE

Panelfold vinyls are easy to clean. Use traditional cleaning methods: i.e. washing, wip- ing, brushing, vacuuming. For water based stains use water based cleaning agents. For oil based stains use solvent cleaner.





OPERABLE PARTITIONS • ACCORDION PARTITIONS
PORTABLE PANEL PARTITIONS • ACOUSTICAL PANELS • FOLDING DOORS

Panelfold, Inc. PO Box 680130 Miami, Florida 33168 • Phone: 305-688-3501 • FAX: 305-688-0185
E-Mail: sales@panelfold.com • Internet: www.panelfold.com

See our other color selections cards for additional textured vinyls, wood veneers, acoustical wall carpetings, woven fabrics and high pressure laminates available for use on Panelfold Innovative Space Division Systems.